

Item Number EB16514745

https://www.eibabo.us/berker/push-button-sensor-double-glass-black-knx-touch-sensor-4-fold-7516259 2-eb16514745



Push button sensor double glass black - KNX touch sensor 4-fold 75162592

×

Berker 75162592

4011334372103 EAN/GTIN

146,82 USD excl. VAT**

plus **shipping**



15-16 days* (USA)

Push-button sensor 2-fold glass black 75162592 bus system KNX, other bus systems without, type of installation flush-mounted, with theft/dismantling protection, number of actuation points 4, number of buttons 2, with LED display, material glass, material quality other, surface lacquered, surface finish glossy, Color black, RAL number (similar) 9005, degree of protection (IP) IP20, push button sensor 2gang comfort B.IQ glass, black. 2-gang comfort B.IQ push button with anti-dismantling protection, with one operating and four status LEDs. Flush installation. The 2-way comfort touch sensor is an instabus user module. It is used to plug onto a bus coupler Up. Dismantling protection is provided by screwing the push button sensor to the flush-mounted bus coupler. The data exchange between the push button sensor and the bus coupler takes place via the user interface (AST). Each push of a button on the 2-fold push button sensor causes the bus coupler to generate a telegram and send it to the bus. The telegram format depends on the parameterization of the application. Depending on the selected parameterization, switching, dimming, blind and value transmitter functions can be combined as desired. Application properties: Button functions: buttons, switching in toggle mode, dimming one/two-surface operation, blind control one/two-surface operation, value transmitter 1-byte function, light scene extension with value transmitter 1-byte function, light scene recall with/without memory function, brightness value transmitter, temperature value transmitter 2 Byte, cyclic sending, control function, forced operation. Additional functions: Two operating levels, second operating level with selectable reduced functionality, switchover of operating levels via object. LED: Status LED per button, operation LED. Protection against dismantling: with mechanical protection against dismantling.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE



In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

