



Touch sensor double glass polar white - KNX touch sensor 4-fold 75642060



Berker
75642060
4011334383697 EAN/GTIN

381,11 USD excl. VAT**
plus shipping



15-16 days* (USA)

Touch sensor double glass polar white 75642060 bus system KNX, other bus systems without, type of installation flush-mounted, with theft/dismantling protection, with bus coupling, number of actuation points 4, number of buttons 0, with LED display, with display, material glass, material quality other, surface other, Glossy surface design, color white, RAL number (similar) 9010, with room thermostat, degree of protection (IP) IP20, min. depth of the device socket 16mm, 2-fold touch sensor with temperature controller R.1 glass, polar white. Touch sensor 2x with temperature controller with all-round chamfer, with rounded corners, without visible fastening elements, with four control surfaces, LED display with symbols for showing the operating mode, controller lock, room outside temperature, time (timer required), with 2 additional display sensor surfaces, with a blue operating LED, with four white status LEDs. Concealed installation, special program. Operating element for room-related and room-spanning control of functions. For individual individual room temperature control, actuation by touching the glass plate (capacitive detection), flat design and high switching reliability through application of the conductor tracks directly to the glass plate, for installation in a 2-way installation box. For vertical installation, with removal tool, with integrated bus coupler, bus connection via connection terminal. The scope of the display menu for operation can be parameterised. For switch pushbutton dim blind room temperature controller functions, value transmitter for dimming position brightness and temperature values 1 and 2 bytes, one and two surface operation configurable, sensor surfaces can be blocked via object, controller operating modes: comfort standby night and frost/heat protection mode. For heating and/or cooling operation with/without additional stage, control parameters for heating or cooling elements are preset. For continuous (PI) or switching (2-point) control, temperature measurement via internal and/or external, connectable sensors with averaging, message objects for heating and cooling, with valve protection function, object for controller status, with key lock function.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

