

LED line light 3.8W 4000K - Ceiling-/wall luminaire 451156.002.1


RZB

451156.002.1

4051859035725 EAN/GTIN



19,50 USD excl. VAT**
plus shipping



4-5 days* (USA)

LED line light 3.8W 4000K 451156.002.1 Suitable for wall mounting, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not interchangeable, With light source, Suitable for light line configuration, Suitable for number of light sources 1, Other socket, Housing material plastic, Housing color white, Material of the cover plastic transparent, design of the louvre without, voltage type AC, nominal voltage 220 ... 240V, control gear current-controlled LED control gear, with control gear, without dimming function, other light distributor, symmetrical light distribution, beam angle unshielded/diffuse, light emission direct/indirect, rated service life L70/B50 at 25 °C 25000h, degree of protection (IP) IP20, degree of protection (NEMA) other, impact resistance IK02, protection class II, rated ambient temperature according to IEC62722-2-1 25 ... 25°C, glow wire test according to IEC 60695-2-11 750 °C - 30 s, suitable for lamp power 4 ... 4W, max. system power 4W, rated luminous flux according to IEC 627 22-2-1 420lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 105lm/W, width 23mm, height/depth 37mm, length 275mm, type of wiring with through-wiring, connection type other, classic T5 Striplight series now expanded with the latest LED technology. Universally applicable in the shop area, light coves, kitchen and bathroom. Prismatic lamp cover for excellent light distribution. Simple assembly using the clip system. Continuous row mounting possible without gaps (12 lights). Suitable for attachment and installation in furniture. Included in delivery: supply cable 1, 80 m, connecting cable 150 mm, straight coupling rigid and 2 brackets each for wall and ceiling mounting. Light color 840. LED service life 25,000 h (L70, B50). Very compact line light with rocker switch and MM sign. Suitable for almost any interior design application. White plastic housing. Plastic prismatic cover. Built-in operating device. Bulbs (LED) included. Built-in LED. Through-wiring using connecting cables (optional) can be produced without tools. With mains connection cable L 1800 mm, connecting cable L 160 mm, straight coupling and a few clip holders each for wall and ceiling mounting (the luminaire assembly and tool-free maintenance are very easy to implement with these). A maximum of 12 lights are permitted as a light band!

YOUR ADVANTAGES


WORLDWIDE TRADE

Corporate video eibmarkt®


99% CUSTOMER SATISFACTION

> 500,000 customers worldwide


DHL TRACK & TRACE

Shipment tracking


COMPLAINTS HANDLING

Obliging and 100% safely


25 YEARS OF EXPERIENCE

In worldwide mail order


ORDER LIVE CHAT

With order history


SHORT DELIVERY TIME

Warehousing


REFUND

Within 14 days


DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

