×



Item Number EB10785567

 $https://www.eibabo.us/siemens/consumer-feeder-400vac-4.5-6.3a-230v-motor-starter-combination-2-2 \\kw-3ra2110-1ga15-1ap0-eb10785567$



Consumer feeder 400VAC 4.5-6.3A 230V - Motor starter combination 2,2kW 3RA2110-1GA15-1AP0

Siemens

3RA2110-1GA15-1AP0 4011209794139 EAN/GTIN

109,94 USD excl. VAT**

plus **shipping**



15-16 days* (USA)

Load feeder 400VAC 4.5-6.3A 230V 3RA2110-1GA15-1AP0 Type of motor starter Other, With short-circuit release, Rated control supply voltage Us at AC 50 Hz 230 ... 230V, Rated control supply voltage Us at AC 60 Hz 230 ... 230V, Rated control supply voltage Us at DC 0V, type of voltage for actuation AC, rated operational power at AC-3, 400 V 2.2kW, rated operational current le 4.9A, rated operational current at AC-3, 400 V 4.9A, overload release current setting 4.5 ... 6.3A, Tripping class CLASS 10, connection type main circuit screw connection, type of coordination according to IEC 60947-4-3 class 1, number of indicator lights 0, degree of protection (IP) IP20, width 45mm, height 167mm, depth 97mm, load feeder without fuse, direct starting AC 400 V, size S00 4.50...6.30 A AC 230 V Screw connection for DIN rail mounting Type of coordination 1, Iq = 150 kA 1 NO (contactor) SIRIUS 3RA21 direct starter for protecting and starting motors. The 3RA21 direct starter is a tested and factory-assembled Combination of a 3RV2 motor starter protector and a 3RT2 contactor, which are already fully wired and mechanically and electrically connected. They are climate-proof, approved worldwide (e.g. IEC and UL/CSA) and IE3/IE4 ready. The 3RA2 load feeders are available with AC and DC operation in sizes S00, S0 and S2 with setting ranges from 0.14 to 65A available. They are offered with screw and spring-loaded connection technology for mounting on DIN rails, screw fastening and mounting on 60 mm busbars. In addition, we offer more than 40,000 other tested combinations of individual devices for protecting, switching and starting a wide variety of applications up to 630 A. All the accessories for the 3RV2 circuit breakers and 3RT2 contactors are the same for all sizes and can also be used for the load feeders. The optional SIRIUS 3RV29 infeed system (for S00 and S0) reduces the amount of wiring considerably. The 3RA21 load feeders replace the tried-and-tested 3RA11 series. Simple, efficient, always up-to-date - the SIRIUS modular system

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLING *Obliging and 100% safely*



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

