

Item Number EB11104778

https://www.eibabo.us/warema/switch-actuator-knx-sa-8m230-reg-knx-sunblind-shutter-actuator-8-ch-2 014576-eb11104778



Switch actuator KNX SA 8M230 REG - KNX sunblind shutter actuator 8-ch 2014576

×

Warema

2014576 4251317203776 EAN/GTIN

390,73 USD excl. VAT**

plus **shipping**



15-16 days* (USA)

Switch actuator KNX SA 8M230 REG 2014576 bus system KNX, other bus systems without, mounting type REG, width in modular units 6, with bus coupling, local/manual operation, with LED display, switching current ohmic 2.1A, max. switching capacity 500W, max. number of Blind outputs 8, type of current AC, degree of protection (IP) IP30, two sun protection drives with 230 V AC can be switched with the WAREMA KNX SA 8M230 sun protection actuator in the REG housing. Emergency/manual operation via safety mat for diagnosis and operation on the actuator. Easily replaceable fine-wire fuses ensure optimum cable protection for the connected components in the event of a short circuit. Preset basic parameters for selecting blind/venetian blind operation, roller shutter/textile sun protection or window awning with ZIP guidance. The three global security objects and one additional security object per output with different priorities and cyclic monitoring can be freely assigned and the reaction to security objects in the event of an alarm or after an alarm can be selected. With the actuator it is possible to switch on external automatic systems. For this purpose, the manual and automatic input are separated in terms of blind height and slat position. There is also the option of restricting manual operation using the automatic objects (cut off, etc.). Received telegrams can be saved and made up for during the automatic switch-off, and you can also define a status after the switch-off. The actuator has 8 scene objects per output. Status of hanging height, status of holding time, status of upper end position reached and slat angle can be sent or read out for each output. Creeping speed can be parameterized when starting the engine. It is possible to set correction times/delay time when approaching.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

