



Contactor 132KW/400V,3pol. - Magnet contactor 265A 220...240VAC 3RT1265-6AP36



Siemens
3RT1265-6AP36
4011209508934 EAN/GTIN

1515,59 USD excl. VAT**
plus shipping



15-16 days* (USA)

Contactor 132KW/400V,3pol. 3RT1265-6AP36 Rated control supply voltage Us at AC 50 Hz 220 ... 240 V, rated control supply voltage Us at AC 60 Hz 220 ... 240 V, rated control supply voltage Us at DC 220 ... 240 V, type of voltage for actuation AC/DC, rated operational current Ie at AC-1, 400 V 330A, rated operational current Ie at AC-3, 400 V 265A, rated operational power at AC-3, 400 V 132kW, rated operational current Ie at AC-4, 400 V 230A, rated operational power at AC-4, 400 V 132kW, rated operational power NEMA 147,09975kW, suitable for series installation, number of auxiliary contacts as NO contacts 2, number of auxiliary contacts as NC contacts 2, connection type main circuit rail connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, vacuum contactor, AC-3 265 A, 132 kW / 400 V AC (50-60 Hz) / DC operation UC 220-240 V Auxiliary contacts 2 NO + 2 NC 3-pole, size S10 Busbar connections Drive: conventional SIRIUS 3RT12 vacuum contactor for switching motors. The vacuum contactors 3RT12 are part of the SIRIUS modular system with its perfectly matched products. They impress with their high performance combined with a compact design and high contact reliability. The vacuum contactors are also characterized by a particularly long switching life. They are therefore particularly suitable for frequent switching in jog mode. They can be combined with other components in the load feeder in a variety of ways. The contactors offer the right connection to the controller for every application (directly or via PLC input). Pre-assembled auxiliary switches reduce the complexity of your setup. The 3RT1 contactors are climate-proof, approved worldwide (eg IEC and UL/CSA) and IE3/IE4ready. They are available in various sizes and in a large power range. They have a wide DC voltage range and a PLC control input. In the main circuit, the devices can be connected via rails or box terminals. For the auxiliary and control circuits, they are also available with a spring-loaded connection for a fast, maintenance-free and vibration-proof connection. There is a wide range of accessories for these contactors, such as wiring kits that significantly reduce the wiring effort, auxiliary switches or terminal covers. Simple, efficient, always up to date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

