



Position switch with roller plunger - Roller cam switch IP67 LS-11/P



Eaton
 LS-11/P
 266112
 4015082661120 EAN/GTIN

28,55 USD excl. VAT**
 plus shipping



4-5 days* (USA)

Position switch with roller plunger LS-11/P sensor width 31mm, sensor diameter 0mm, sensor height 61mm, sensor length 33.5mm, rated operational current Ie at AC-15, 24 V 6A, rated operational current Ie at AC-15, 125 V 6A, rated operational current Ie at AC-15, 230 V 6A, rated operational current Ie at DC-13, 24 V 3A, rated operational current Ie at DC-13, 125 V 0.8A, rated operational current Ie at DC-13, 230 V 0.3A, Switching function Slow-action switching element, positive opening, number of safety-related auxiliary contacts 1, number of contacts as NC contacts 1, number of contacts as NO contacts 1, number of contacts as change-over contacts 0, design of the interface without, design of the interface for safety-related communication without, cuboid housing design, material of the Housing plastic, coating housing other, design of the actuating element roller tappet, alignment of the actuating element other, design of the electrical connection other, suitable for r Safety functions, explosion protection category for gas without, explosion protection category for dust without, ambient temperature during operation 25 ... 70°C, degree of protection (IP) IP67, degree of protection (NEMA) 4X, position switch, basic function: position switch, safety position switch, Type code: LS(M)-..., range: roller plunger, degree of protection: IP66, IP67, equipment: complete device, ambient temperature: -25 - +70 °C, design: EN 50047 form C, contact configuration S = NO contact: 1 NO, contact configuration NC = NC contact: 1 NC, note: = safety function, through positive opening according to IEC/EN 60947-5-1, positive opening (ZW): yes, housing cover color: yellow, housing: plastic, connection type: cage clamp, cage clamp is a registered trademark of the company Wago Kontakttechnik, 32432 Minden., Accessories for the cage-clamp connection from the company Wago: insertion bridge, grey, Wago order no. 264-402, standards and regulations: IEC/EN 60947

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

