×



Item Number EB11600729

https://www.eibabo.us/maico/axial-wall-fan-wall-plate-dn-200-two-way-industrial-fan-200mm-dzq-20-2-b-eb11600729



Axial wall fan wall plate DN 200 - Two-way industrial fan 200mm DZQ 20/2 B

MaicoDZQ 20/2 B
0083.0116
4012799831167 EAN/GTIN

551,11 USD excl. VAT**

plus shipping



15-16 days* (USA)

Axial wall fan wall plate DN 200 DZQ 20/2 B mains frequency 50Hz, rated voltage 400V, conveyor temperature -20... 60°C, volume flow 1150m³/h, speed 28501/min, protection class (IP) IP55, ventilation version, nominal width 200mm, closure flap without, protective grille on the suction side, yellow chromated, contact protection according to DIN EN ISO 13857. 8-blade impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Installation possible in any position. Conveying direction: The following figure shows the conveying direction: Conveying direction A: Suction via the motor, standard. Conveying direction B: Blowing via the motor, on request. Direction of rotation, reversing operation: The volume flow decreases by approx. 35% if the conveying direction is abnormal. Motor: asynchronous motor. Speed controllable. Exception: Type EZQ 45/6 B, EZS 45/6 B, DZQ 40/2 B and DZS 40/2 B. Reversible. Exception: Fans with shaded-pole motors (...-E). Not suitable for pumping air saturated with water vapor. Three-phase motor: DZQ and DZS series. Rated voltage 400 V, 50 Hz. Protection class IP 55. Exception DZQ/DZS... D IP 54. Thermal overload protection as standard. Exception: Available on request for DZQ/DZS 25/4 D and pole-changing axial wall fans. The connections are potential-free on terminals and must be connected to a full motor protection switch, e.g. MV 25, or the control circuit of a contactor. Pole-changing fans: Ensure overload protection with a full motor protection switch to be provided on site. Pole-changing motors with speed ratios of 8/4 or 4/2 are connected using the Dahlander principle. Electrical connection: To the terminal strip in the end cover of the motor. Safety instructions: The fan may only be put into operation if contact protection of the impeller is guaranteed in accordance with DIN EN ISO 13857. Article: DZQ 30/2 B, design: square wall plate, delivery volume: 3640 m3/h, nominal delivery volume: 2520 m3/h / in opt. Efficiency, pressure pfs, nominal: 190 Pa - in opt. Efficiency, speed nnominal: 2810 1/min - in opt. Efficiency, speed: 2851 1/min, impeller type: axial, speed controllable: yes, reversibility: yes, voltage type: threephase current, rated voltage: 400 V, mains frequency: 50 Hz, nominal power: 375 W / in opt. Efficiency, Irated: 0.85 A / in opt. Efficiency, IMax: 1.1 A, protection class: IP 55, thermal class: B, power supply cable: 7 / 1.5 mm2 location: wall / ceiling, installation type: surface-mounted, installation position: horizontal / vertical, material: sheet steel, galvanized, weight: 11.6 kg....

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

