



Exhaust element - Inside in-/outlet for ventilation Centro-E



Maico
 Centro-E
 0084.0183
 4012799841838 EAN/GTIN

224,65 USD excl. VAT**
 plus shipping



15-16 days* (USA)

Exhaust air element Centro-E, nominal width=75 mm, volume flow=65 m³/h, color=white, medium temperature=-20..40 °C, type of installation=flush-mounted, rated voltage=230 V, mains frequency=50 Hz, configuration=other, nominal current =0.9 A, housing material=plastic, direction=axial, protection class (IP)=other, width=251 mm, height=251 mm, depth=138 mm, exhaust air element Centro-E - electrical version: exhaust air element with electrothermal actuator . For basic and demand ventilation. Central fan pressure control required. Electrical plug-in connection for quick installation of the exhaust air element in the housing. MAICO Centro-E exhaust air elements comply with protection class IP X5 and can therefore be installed in area 1 according to DIN VDE 0100-701, even with jets of water. Protection class II. Exhaust air element with cover and G2 filter for installation in flush-mounted housing. Can be used with Centro central ventilation system. Fire protection identical to MAICO ER single room ventilation. No cold smoke barriers necessary. No additional silencers necessary. Color traffic white, similar to RAL 9016. Easy filter change without tools. Cover can be rotated by +- 5°, allowing compensation if the housing is inserted at an angle. Installation-friendly snap-on fastening of the exhaust air element in the housing. Shaft level difference according to DIN 4109, tested by IAB Oberursel. Item: Centro-E, design: electric, delivery volume: 30 m³/h / 65 m³/h, minimum delivery volume: 30 m³/h, air direction: ventilation, type of voltage: alternating current, rated voltage: 230 V, mains frequency: 50 Hz / 60 Hz, Power consumption: 3 W, IMax: 0.9 A, degree of protection: IP X5, mains cable: 3 / 1.5 mm², installation location: wall / ceiling, installation type: flush-mounted, system type: central, material: plastic, colour: traffic white, similar to RAL 9016, weight: 0.8 kg, filter class: G2, width: 251 mm, height: 251 mm, depth: 138 mm, conveying medium temperature at IMax: 40 °C, sound pressure level: 26 dB(A) / 33 dB(A) / Specification according to DIN 18017-3 with an equivalent absorption area AL = 10 m², nominal width: 75 mm / 80 mm

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

