

## Item Number EB12903816

https://www.eibabo.us/siemens/toggle-switch-1-no-contact-1-no-toggle-switch-2no-0nc-3su1150-2bl60-1na0-eb12903816



## Toggle switch 1 NO contact, 1 NO - Toggle switch 2NO/0NC 3SU1150-2BL60-1NA0

×

## Siemens

3SU1150-2BL60-1NA0 4011209956513 EAN/GTIN

**22,30 USD** excl. VAT\*\*

plus **shipping** 



15-16 days\* (USA)

Selector switch 1NO, 1NO 3SU1150-2BL60-1NA0 Number of switch positions 3, Design of the toggle actuator, Suitable for lighting, Color of the button white, Hole diameter 22.3mm, Width of the opening 32.3mm, Height of the opening 28.8mm, Switching function latching, Degree of protection (IP) IP67/IP69K, degree of protection (NEMA) 13, supply voltage 5 ... 500V, number of contacts as NO contact 2, number of contacts as NC contact 0, number of contacts as changeover contact 0, design of the electrical connection other, with front ring, Front ring material other, front ring color other, toggle switch, illuminated, 22 mm, round, metal, high-gloss, white, toggle, short, 3 switch positions IO-II, latching, switching angle 2x45°, 10:30h/12h/13:30h, with holder, 1NO, 1NO, screw connection SIRIUS ACT toggle switch for switching and controlling electrical loads. Under the brand name SIRIUS ACT, Siemens offers a unique portfolio of commanding and signaling devices with global product approvals in Four modern design series made of robust real metal and high-quality plastic. The innovative snap-on concept simplifies assembly to such an extent that only one hand and no special tools are required. Groove-free holes are sufficient as mounting holes, as 100% anti-twist protection is already integrated. Thanks to the consistently high degree of protection, the robust devices are suitable for industrial use and for outdoor use. Even cleaning with a high-pressure jet is possible. Neither dust, oil nor aggressive alkalis can disrupt reliable operation. In addition to the standard wiring, the devices can also be connected to the controller via PROFINET, AS-Interface or IO-Link. This reduces your wiring effort, minimizes sources of error and gains more flexibility. The graphic online configurator provides convenient support when selecting and ordering individual devices, housings and labels. Extensive documentation (e.g. manual, 3D data, connection diagram) is available versions: several colours, 2-4 switching positions, short/long tog

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- \*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

