



**P-LED recessed floor light IP67 230V 5.5W 7000K - In-ground luminaire 1x0,1...9W 677010.061**



**EVN**  
677010.061  
4037293002905 EAN/GTIN

**83,88 USD** excl. VAT\*\*  
plus shipping



15-16 days\* (USA)

P-LED recessed floor light IP67 230V 5.5W 7000K 677010.061 Energy efficiency class of the supplied replaceable light source A+, Highest energy efficiency class of the replaceable light source A++, Lowest energy efficiency class of the replaceable light source E, Energy efficiency class spectrum A++ to E, Light source LED replaceable, With light source, Suitable for number of light sources 1, socket GX53, housing color stainless steel, cover material transparent glass, type of voltage AC, nominal voltage 230 ... 230V, nominal LED current at constant current 0mA, control gear not required, without dimming function, light distribution symmetrical, beam angle unshielded/diffuse, protection class (IP) IP67, protection class I, suitable for lamp power 0.1 ... 9W, max. system power 6W, rated luminous flux according to IEC 62722-2-1 470lm, light color white, color temperature 6000 ... 6000K, color rendering index CRI 80-89, width 0mm, height / depth 68mm, length 0mm, outer diameter 119mm, installation width 0mm, installation h Height/depth 70mm, installation length 0mm, installation diameter 114mm, max. load 2000kg, can be rolled over, type of wiring suitable for through-wiring, the luminaire body made of die-cast aluminum is covered with polyester, while the cover plate is made of V4A stainless steel. With the 2 cable glands on the side, which are suitable for cables with a diameter of up to 9mm, it is possible to wire several lights through, which makes installation much easier for longer cable runs. It is possible to mount the lamp without the plastic installation pot included in the scope of delivery, in this case the installation depth is 66mm and the required hole cutout is 104mm. The cable entry into the installation pot is from below. The supplied LED bulb can be replaced at any time if necessary. The maximum crossing speed is 25km/h.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

