



Soft starter 12,5A 110...230VAC 3RW4024-1BB14


Siemens

3RW4024-1BB14

4011209691582 EAN/GTIN

397,89 USD

excl. VAT**
plus shipping


4-5 days* (USA)

Soft starter Sirius 12.5A 3RW4024-1BB14 Rated operating current I_e at 40 °C Tu 12.5A, rated operating voltage U_e 200 ... 480V, rated power three-phase motor, standard circuit, at 230 V 3kW, rated power three-phase motor, standard circuit, at 400 V 5.5kW, function one direction of rotation, rated ambient temperature without derating 40°C, rated control supply voltage U_s at AC 50 Hz 110 ... 230V, rated control supply voltage U_s at AC 60 Hz 110 ... 230V, rated control supply voltage U_s at DC 110 ... 230V, voltage type for actuation AC/DC, Integrated overload protection of the motor, protection class (IP) IP20, SIRIUS soft starter S0 12.5 A, 5.5 kW/400 V, 40 °C AC 200-480 V, AC/DC 110-230 V screw terminals SIRIUS 3RW40 soft starter for standard applications for smooth starting and stopping of three-phase asynchronous motors. Continuously variable starting, reducing current peaks, avoiding mains voltage fluctuations during startup, relieving the load on the power supply network, reducing the mechanical load on the drive, significant space and wiring savings compared to star-delta starters and frequency converters, maintenance-free switching and extremely easy handling. The integrated bypass enables the very compact design and ensures less heating in the control cabinet. Intelligent monitoring functions protect the soft starter from overheating and the motor from overload. You can also limit the current to an adjustable maximum value during startup. With the integrated remote reset, you can quickly and easily troubleshoot problems remotely. Worldwide approvals (e.g. IEC and UL/CSA) also for potentially explosive applications (ATEX or IEC Ex). The 3RW soft starters are available for networks up to 690 V in a wide power range with different control supply voltages and consistently with screw and spring-loaded connections. The 3RW30/40 has additional variants with 24 V control supply voltage. Some of the 3RW40 up to size S3 and all 3RW44 also offer thermistor motor protection. With the optional connection module, the soft starters can be attached to the circuit breakers, even for the variants with a spring-loaded connection. The optional fan enables an even tighter design in the control cabinet. Simple, efficient, always up to date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



COMPLAINTS HANDLING

Obliging and 100% safely



SHORT DELIVERY TIME

Warehousing



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



25 YEARS OF EXPERIENCE

In worldwide mail order



REFUND

Within 14 days



DHL TRACK & TRACE

Shipment tracking



ORDER LIVE CHAT

With order history



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

