https://www.eibabo.us/tcs/video-front-door-station-2-buttons-1-row.ap-si-door-station-door-communication-2-button-avc1102...-eb17108151

Video front-door station 2 buttons 1-row.AP si - Door station door communication 2-button AVC1102...

TCS
AVC11020-0010
4035138028431 EAN/GTIN

739,19 USD excl. VAT**

plus **shipping**

15-16 days* (USA)

Video front-door station 2 buttons 1-row.AP si AVC11020-0010 Installation technology bus system, surface-mounted installation, number of call buttons 2, with cover, protection against vandalism, with camera, material aluminium, color silver, height 175mm, width 104mm, depth 16mm, TCS video front-door station for surface mounting, AVC11020-0010 with 2 bell buttons, item number: AVC11020-0010, image / VIDEO PROPERTIES, color camera with CCD sensor, day/night switching: automatic, infrared lighting for close-range illumination, diagonal detection angle: 90 degrees, Resolution: 380 TVL, focal length: f = 3.6 mm, light sensitivity: 0.2 lux, device properties, video outdoor station, number of bell buttons: 2, mounting type: surface mounting, housing type: surface mounting, integrated loudspeaker, housing material: aluminum, housing color : natural anodised, bell button material: metal with maintenance-free contacts, shatterproof nameplate glass, sensor-controlled nameplate lighting, opening principle: win:clip, volume ke voice output: adjustable, volume of microphone sensitivity: adjustable, extended features, light switch function: on unprogrammed bell button, name field: white backlit, number of wires: 6-wire required, installation mix audio, video, access to a system: possible, commissioning and configuration: manual, with service device, system configuration memory: permanently integrated, technical data, technology: 2-wire TCS:BUS, current consumption, at rest: in 6-wire operation i(a) = 0.14 mA, I(P) = 50 mA, current consumption , maximum: i(Pmax) = 50 mA, surface-mounted housing HxWxD mm: 175x104x16, camera field HxW mm: 36x72, name plate HxW mm: 24x68, information plate HxW mm: 32x68, recommended mounting height: 1.6 m, permissible ambient temperature: -20 to + 50 degrees C, UV resistance: unrestricted, scope of delivery, for changing the name badges: win:clip key, for labeling: name badges

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online