



**Headlight sgr axsym.breitst. - Spot light/floodlight 1x70W  
8870051000**



**Meyer + Sohn**  
8870051000  
4022644151340 EAN/GTIN

**325,10 USD** excl. VAT\*\*  
plus shipping



15-16 days\* (USA)

Headlight sgr axsym.breitst. 8870051000, Surface mount suitable=No, Recess mount suitable=No, Wall mount suitable=Yes, Pendant suitable=No, Ceiling mount suitable=Yes, Truss mount suitable=Yes, Pedestal/floor mount suitable=Yes, Track mount suitable =no, suitable for clamp mounting=no, suitable for cable system=no, adjustability=rotatable and pivotable, with motion detector=no, with light sensor=no, illuminant=metal halide lamp/sodium vapor lamp, with illuminant=no, suitable for number of illuminants=1, Socket=RX7s, housing material=aluminium, surface=powder-coated, housing color=silver, cover material=glass transparent, surface brushed=no, type of voltage=AC, nominal voltage=230 V, with control gear=yes, dimming dependent on control gear=yes, dimming 0-10 V=no, dimming 1-10 V=no, dimming DALI=no, dimming DMX=no, dimming DSI=no, dimming potentiometer (device-integrated)=no, dimming GPRS=no, dimming LineSwitch=no in, dimming manufacturer-specific=no, dimming mains voltage modulation=no, dimming trailing edge=no, dimming leading edge=no, dimming programmable=no, dimming RF=no, dimming Sine Wave Reduction=no, dimming Touch and Dim=no, dimming Zigbee=no, dimming with push button=no, without dimming function=yes, reflector=high-gloss, light distribution=symmetrical, protection class (IP)=IP65, impact resistance=IK08, protection class=I, suitable for lamp power=70 W, light color=white, light with limited surface temperature "D mark"=no, suitable for VDU workstations according to EN 12464-1=no, covering the lamp with thermal insulation material possible=no, for metal halide lamps (HIT-DE), ceramic burner lamps (HIT-DE-CE) and high-pressure sodium vapor lamps (HST-DE) Protection class I, IP65, IK08 Luminaire made of die-cast aluminium, polyester powder-coated, axisymmetric aluminum reflector, highly specular, all outer steel parts are rust-free, temperature-resistant safety glass, sili conseal, mounting bracket made of coated aluminum with inclination scale: 2 holes, diameter 8.5 mm, distance 70 mm, 1 central hole, diameter 17 mm, inclination range 120 degrees, cable connection: PG 11, through-wiring on request, ballast and ignitor built-in, uncompensated, compensation on request, standard without lamp

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

