



## Halogen headlights black st 500W - Spot light/floodlight 1x500W 8509041000



**Meyer + Sohn**  
8509041000  
4022644117148 EAN/GTIN

**96,02 USD** excl. VAT\*\*  
plus shipping



15-16 days\* (USA)

Halogen spotlight sw st 500W 8509041000, suitable for surface mounting=no, suitable for recessed mounting=no, suitable for wall mounting=yes, suitable for pendulum suspension=no, suitable for ceiling mounting=yes, suitable for truss mounting=yes, suitable for pedestal/floor mounting =yes, suitable for track mounting=no, suitable for clamp mounting=no, suitable for cable system=no, adjustability=rotatable and pivotable, with motion detector=no, with light sensor=no, illuminant=HV halogen lamp, with illuminant=no, suitable for Number of bulbs=1, socket=R7s, housing material=aluminium, surface=powder-coated, housing color=black, cover material=glass transparent, surface brushed=no, type of voltage=AC, nominal voltage=230 V, with control gear=yes, dimming dependent from control gear=yes, dimming 0-10 V=no, dimming 1-10 V=no, dimming DALI=no, dimming DMX=no, dimming DSI=no, dimming potentiometer (device-integrated)=no, dimming GPRS=no, dimming LineSwit ch=no, dimming manufacturer-specific=no, dimming mains voltage modulation=no, dimming trailing edge=no, dimming leading edge=no, dimming programmable=no, dimming RF=no, dimming Sine Wave Reduction=no, dimming Touch and Dim=no, dimming Zigbee =no, dimming with push button=no, without dimming function=yes, reflector=high-gloss, light distribution=symmetrical, protection class (IP)=IP55, impact resistance=IK07, protection class=I, suitable for lamp power=500 W, light color=white, Width=260 mm, height/depth=110 mm, length=210 mm, lamp with limited surface temperature "D-sign"=no, suitable for computer workstations according to EN 12464-1=no, the lamp can be covered with thermal insulation material=no , For halogen bulbs (QT-DE 12) Protection class I, IP55, IK07 Luminaire made of die-cast aluminium, polyester powder-coated, axisymmetric aluminum reflector structure, polished, all outer steel parts are rust-free, temperature-resistant safety glass, silicone seal, small frame appbar, mounting bracket made of hot-dip galvanized steel, 2 holes with a diameter of 9 mm, distance 70 mm, 1 central hole with a diameter of 10.5 mm, inclination range 100 degrees, cable connection: PG13.5, without lamp as standard, mounting bracket made of hot-dip galvanized steel

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

