



Fan - Conduit mounted ventilator 1100m³/h 65W EZR 20/2 B



Maico
 EZR 20/2 B
 0086.0000
 4012799860006 EAN/GTIN

684,87 USD excl. VAT**
 plus shipping



15-16 days* (USA)

Fan EZR 20/2 B, housing material=stainless steel, unloaded air volume=1100 m³/h, connection voltage=230 V, DC motor=no, protection class (IP)=IP55, pole-changing=no, length=240 mm, diameter of the housing =254 mm, pipe sleeve made of galvanized sheet steel, with flange on both sides. 8-blade impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 planes according to quality level 6.3, DIN ISO 1940, Part 1. Flange bores according to DIN EN 12220:1998. DZR 56/6 B and DZR 56/4 B: Flange drilling according to DIN EN 12220:1998. To avoid vibrations being transmitted to the pipe system: Use flexible connectors, feet and vibration dampers. High degree of protection IP 55. Exception EZR/DZR... D IP 54. Can be installed in any position. Motor: asynchronous motor, speed controllable. Exception: Type DZR 40/2 B. Not suitable for conveying water vapor-saturated air. The conveying direction is marked on the device with an arrow indicating the direction of rotation and direction of conveyance. Reversing operation: The volume flow is reduced by approx. 35% if the conveying direction is abnormal. AC motor: EZR series. Rated voltage 230 V, 50 Hz. Capacitor motor with operating capacitor ready for connection in the terminal box. Thermal overload protection as standard. The connections are potential-free on terminals and must be connected to a full motor protection switch, eg MVE 10 (not suitable for EZR 25/4 D, EZR 30/6 B and EZR 35/6 B) or the control circuit of a contactor. Electrical connection: External terminal box with cable grommets. Safety instructions: The fan may only be put into operation if protection against accidental contact with the impeller is guaranteed in accordance with DIN EN ISO 13857. Item: EZR 20/2 B, Delivery volume: 1100 m³/h, Speed: 2850 rpm, Impeller type: Axial, Speed controllable: Yes, Reversibility: Yes, Type of voltage: Alternating current, Rated voltage: 230 V, Mains frequency: 50 Hz, Rated power: 65 W, Irated: 0.3 A, IMax: 0.51 A, type of protection: IP 55, thermal class: B, pole-changing: no, installation position: horizontal / vertical, material: sheet steel, galvanized, weight: 5.9 kg, nominal width : 200 mm, width: 254 mm, height: 317 mm, depth: 240 mm, conveyor temperature at rated current: -20 °C to 60 °C, conveyor temperature at IMax: -20 °C to 60 °C, DC motor: false

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

