

Item Number EB15900036

×

https://www.eibabo.us/siemens/surge-arrester-type-2-350v-surge-protection-for-power-supply-5sd7463 -0-eb15900036

## SIEMENS SND7 403-0 SIEMENS SIEMENS

Surge arrester type 2 350V - Surge protection for power supply 5SD7463-0

**Siemens** 5SD7463-0 4001869340609 EAN/GTIN

## 166,03 USD excl. VAT\*\*

plus shipping



Surge arrester type 2 350V 5SD7463-0 Network configuration TN-C, number of conductors (without earth) 3, rated discharge current (8/20) 40kA, rated voltage AC 230V, short-circuit strength (Isccr) 25kA, maximum continuous voltage AC 350V, max. discharge current (8/20) 40kA, mounting type DIN rail TH35, size 3 HP, protection level 1.4kV, max. conductor cross-section solid (solid/stranded) 35mm<sup>2</sup>, max. conductor cross-section solid (solid/stranded) 35mm<sup>2</sup>, max. conductor cross-section flexible (finely stranded) 25mm<sup>2</sup>, protection level LN 1.4kV, protection level N-PE 1.4kV, signaling on the device without, test class type 2, degree of protection (IP) IP20, surge arrester type 2, requirement class C, UC 350V pluggable protective modules, 3-pin, 3+0 circuit for TNC systems Overvoltage protection devices to protect against overvoltages in electrical systems. The overvoltage protection devices from Siemens, as an important part of the SENTRON protection components for electrical installations, offer effective protection against lightning and overvoltages as a result of atmospheric influences or switching operations. Convenient assembly and connection technology as well as a consistent design are the hallmarks of the device family. Whether for infrastructure or for industrial requirements, Siemens offers surge protection devices for all applications and every area of use. The main features of the Siemens overvoltage protection devices are: 1. Effective investment and system protection against lightning and overvoltages. 2. The right lightning and surge protection included as standard. 5. Tool-free removal for methe top-hat rail. 6. Clear error indication. 7. Data matrix code on the front of the device provides all information about lightning and surge protection for every application of the deside protection induded as standard. 5. Tool-free removal for bothet are: 0. Solid work as a for the device of protection included as standard. 5. Tool-free removal firm the top-hat rail. 6. Clear error indication. 7. Data matr

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

