×



Item Number EB10627340

https://www.eibabo.us/siemens/fi-block-for-circuit-breaker-0.3-40a-3p-0.3a-400v-residual-current-break er-3-p-5sm2632-6-eb10627340



FI block for circuit breaker 0.3-40A 3p 0.3A 400V - Residual current breaker 3-p 5SM2632-6

esiduai current breaker 3-p 55m2632-6

Siemens

5SM2632-6 4001869227290 EAN/GTIN

60,83 USD excl. VAT**

plus **shipping**



15-16 days* (USA)

FI block type A, 300mA, 40A 5SM2632-6 number of poles 3, rated voltage 400V, rated current 40A, rated residual current 300mA, rated insulation voltage Ui 460V, rated impulse withstand voltage Uimp 4kV, mounting type DIN rail, residual current type A, surge current strength 1kA, frequency 50 Hz, additional equipment possible, degree of protection (IP) IP20, width in pitch units 3, installation depth 70mm, ambient temperature during operation -25 ... 45°C, degree of pollution 2, connectable conductor cross-section stranded 1.5 ... 25mm², connectable conductor cross-section stranded 1.5 ... 25mm², connectable conductor cross-section stranded 1.5 ... 25mm², FI block, 3-pole, type A, In: 40 A, 300 mA, Un AC: 400 V, for 5SY The FI switch is the residual current protective device for protection against accidental contact. The patented residual current protective devices from Siemens are an important part of the SENTRON protective devices for electrical installations because they prevent life-threatening electrical accidents by safely switching off dangerous residual currents to earth. Electrically ignited fires can be prevented as soon as they start. Whether by directly touching live parts during operation or by indirectly touching equipment - the protection is primarily achieved by switching off quickly. The main features of the residual current circuit breakers are: 1. Comprehensive protection for people and property against electric shock. 2. Whether sinusoidal AC residual currents or smooth DC residual currents - Siemens offers the right type and special versions for all requirements. 3. Be protected according to standards: All residual current operated circuit breakers comply with DIN VDE regulations. 4. Optimum technology for your safety - only from Siemens. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers a comprehensive portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and socket outlets.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION *Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

