



Residual current circuit breaker with line protection B,6A,1+N,30mA 5SU1356-6KK06



Siemens
5SU1356-6KK06
 4001869306681 EAN/GTIN

35,99 USD excl. VAT**
 plus shipping



15-16 days* (USA)

RCBO type A, 30mA, B6 5SU1356-6KK06 number of poles (total) 2, number of fused poles 1, rated voltage 230V, rated insulation voltage U_i 264V, rated impulse withstand voltage U_{imp} 4kV, rated current 6A, rated residual current 0.03A, residual current type A, Energy limitation class 3, rated breaking capacity according to EN 61009 6kA, rated breaking capacity according to IEC 60947-2 25kA, rated short-circuit breaking capacity I_{cn} according to EN 61009-1 6kA, instantaneous disconnection characteristic, surge current strength 1kA, type of voltage AC, frequency 50 Hz, tripping characteristic B, switching neutral conductor, with locking device, overvoltage category 3, Degree of pollution 2, Ambient temperature during operation -25 ... 55°C, Width in pitch units 2, Installation depth 70mm, Suitable for flush-mounted installation, False tripping protection, Degree of protection (IP) IP20, Connectable conductor cross-section solid 0.75 ... 35mm², Connectable conductor cross-section stranded 0.75 ... 35mm², FI/LS-Sch Iter, 6 kA, 1P+N, type A, 30 mA, B-Char, In: 6 A, Un AC: 230 V FI/LS for combined short-circuit protection and protection against accidental contact. The patented RCBOs from Siemens - as an important component of the SENTRON protective devices for electrical installations, enable combined personal fire and line protection in just one device. In addition to detecting fault currents, they also offer reliable protection against short circuits and overload thanks to the integrated overcurrent protection device. The Siemens RCBOs as a combination of residual current circuit breakers and miniature circuit breakers are characterized above all by: 1. Increased operational reliability and system availability thanks to the separate shutdown of the circuit concerned. 2. Whether sinusoidal AC residual currents or smooth DC residual currents - Siemens offers the right type and special versions for all requirements. 3. Reliable safety during installation thanks to the grip and touch protection included as standard. 4. Tool-free removal from the top-hat rail or from the busbar assembly through convenient slide-hand operation. 5. Clearly visible switch position indicator. 6. Data matrix code on the front of the device provides all information about the RCBO quickly and easily. 7. Be protected according to standards: The RCBOs comply with the provisions of DIN VDE. 8. Optimum technology for your safety - only from Siemens. For the safe, efficient electrical infrastructure in buildings and industry, Siemens offers a comprehensive portfolio of protective switching, measuring and monitoring devices, distribution systems, switches and...

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

