



Contactor 4 NO - Installation contactor 230VAC 4 NO/ 0 NC HS 40-40 230V/50HZ

Doepke
HS 40-40 230V/50HZ
09980414
4014712067165 EAN/GTIN

49,74 USD excl. VAT**
plus shipping

 **4-5 days* (USA)**

Contactor 4 NO contacts HS 40-40 230V/50HZ rated operational voltage 400 ... 400V, rated operational current 40A, utilization category 1, rated operating voltage 230 ... 230V, type of voltage of the operating voltage AC, type of voltage of the operating voltage AC, number of contacts as NO contact 4, number of contacts as opener 0, max. incandescent lamp load 6000W, max. fluorescent lamp load 2975VA, max. fluorescent lamp load (duo circuit) 5280VA, max. A contactor is an electromagnetically actuated remote switch for high electrical power. A larger current can be switched by means of a smaller current. They ensure galvanic isolation between the control circuit and the switched circuit. Installation contactors of the HS series switch very quietly and are extremely low-noise. They are characterized by their long mechanical and electrical service life. Your magnetic coil is suitable for continuous operation (100% ED). Devices of this type are operated with a control voltage of 230 V AC. Properties: large range of different contacts, long electrical and mechanical life, extremely low noise, suitable auxiliary switch and sealing cap available, type of installation: quick mounting on mounting rail, any installation position, areas of application: installation contactors can be used in a variety of residential and commercial buildings as well as industrial plants. They switch incandescent lamps, fluorescent lamps, transformers for low-voltage halogen lamps, high-pressure mercury vapor lamps (HQL, HPL), metal halide lamps (HQL, HPI), low and high-pressure sodium vapor lamps, storage heaters or drives (motors). Notes: The designation of the devices in this series includes both the rated current (first pair of numbers) and the contact design (last pair of numbers): A HS 25-31 has e.g. g. a rated current of 25 A. three NO and one NC contact. The use of the spacer RD 05 is recommended for ambient temperatures above 40 degrees C.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

