×



## Item Number EB10676078

https://www.eibabo.us/schalk/light-time-impulse-switch-with-3-modes-1-no-contact-16a-staircase-lighting-timer-0-25...150min...-eb10676078



Light time impulse switch with 3 modes 1 NO contact 16A - Staircase lighting timer 0,25...150min ...

Schalk

ZSK 2 zsk209

4046929201056 EAN/GTIN

**34,87 USD** excl. VAT\*\*

plus **shipping** 



4-5 days\* (USA)

Light time impulse switch m.3 modes 1S 16A ZSK 2 Electronic function, DIN rail mounting type, width in modular units 1, installation depth 55mm, number of contacts as NO contact 1, number of contacts as NC contact 0, number of contacts as changeover contact 0, control voltage 1 8 ... 230V, type of control voltage 1 AC/DC, frequency of control voltage 1 50 ... 60Hz, control voltage 2 207 ... 253V, type of control voltage 2 AC, frequency of control voltage 2 50 ... 60Hz, rated switching current 16A, off-delay 0, 25 ... 150min, button glow lamp current 20mA, switching type 3- and 4-wire circuit, switch-off pre-warning without, current surge function selectable, downstream switching + continuous light + time extension, supply voltage 207 ... 253V, voltage type of the supply voltage AC, max. incandescent lamp load 1000W, Max. Fluorescent lamp load 250VA, Max. Fluorescent lamp load (duo circuit) 1000VA, Max. Fluorescent lamp load (parallel compensated) 1000VA, The ZSK 2 combines as a modern light time pulse switch (impulse switch) a high degree of comfort, flexibility and variety of functions with easy handling and operation. By briefly or longer pressing the light button, you can choose between two independently adjustable time ranges. This enables individually configurable short-term / long-term switching in a range from 0.25 to 150 minutes. By pressing the light button again, the consumer is switched off immediately. Two operating modes enable the long-term switching to be blocked. As a further special feature, the ZSK 2 includes an additional external voltage input (8V-230V UC) which is galvanically isolated from the other inputs and outputs and which can be controlled, for example, by a door intercom system without a coupling relay, dimensions: 18x55mm, 230V AC - 1 NO contact (potential-free) 16A, tvK/tvL -18/-150min

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE
In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

