



## Power contactor AC-3/400V:4kW 3p DILEM-01 (400V50HZ) - Magnet contactor 9A 400VAC 0VDC DILEM-01(4...



**Eaton**  
DILEM-01(400V50HZ)  
051797  
4015080517979 EAN/GTIN

**33,59 USD** excl. VAT\*\*  
plus shipping

 15-16 days\* (USA)

Power contactor AC-3/400V:4kW 3p DILEM-01(400V50HZ) rated control supply voltage  $U_s$  at AC 50 Hz 400 ... 400V, rated control supply voltage  $U_s$  at AC 60 Hz 440 ... 440V, rated control supply voltage  $U_s$  at DC 0V, type of voltage for actuation AC, Rated operational current  $I_e$  at AC-1, 400 V 22A, rated operational current  $I_e$  at AC-3, 400 V 9A, rated operational power at AC-3, 400 V 4kW, rated operational current  $I_e$  at AC-4, 400 V 6.6A, rated operational power at AC-4, 400 V 3kW, rated operational power NEMA 3.7kW, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NC contact 1, connection type main circuit screw connection, number of NC contacts as main contacts 0, number of NO contacts as main contacts 3, power contactor, application: miniature contactor for motors and resistive loads, contactors DILEM, Utilization category: AC-1: Non-inductive or weakly inductive load, resistance furnaces, AC-3: Squirrel-cage motors: starting, switching off during operation, AC-4: K Squirrel-cage motors: starting, counter-current braking, reversing, jogging, connection technology: screw terminals, note: also suitable for motors of efficiency class IE3., IE3-capable devices are marked with the logo on the packaging., Description: with auxiliary switch, poles: 3-pole, Rated operational current AC-3 380 V 400 V:  $I_e = 9$  A, Rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C:  $I_{th} = I_e = 22$  A, encapsulated:  $I_{th} = 16$  A, Rated operational current AC-1 conventional thermal current 1-pole open:  $I_{th} = 50$  A, encapsulated:  $I_{th} = 40$  A, max. rated operational power of three-phase motors 50 - 60 Hz AC-3 220 V 230 V:  $P = 2.2$  kW, 380 V 400 V:  $P = 4$  kW, 660 V 690 V:  $P = 4$  kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V:  $P = 1.5$  kW, 380 V 400 V:  $P = 3$  kW, 660 V 690 V:  $P = 3$  kW, can be used for: ...DILE, contact equipment NC = NC contact: 1 NC, type of current AC/DC: alternating current operation

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

