



## Main switch I2/SVB - Safety switch 3-p 15kW P1-32/I2/SVB/Hi11



**Eaton**  
P1-32/I2/SVB/Hi11  
207318  
4015082073183 EAN/GTIN

**78,55 USD** excl. VAT\*\*  
plus shipping



4-5 days\* (USA)

Main switch I2/SVB P1-32/I2/SVB/Hi11 Design as a main switch, design as a maintenance/repair switch, design as a safety switch, design as an EMERGENCY STOP device, number of switches 1, max. rated operating voltage Ue at AC 690V, rated operating voltage 690 ... 690V, rated uninterrupted current Iu 32A, rated uninterrupted current at AC-23, 400 V 32A, rated uninterrupted current at AC-21, 400 V 32A, rated operational power at AC-3, 400 V 13kW, rated short-time withstand current Icw 0.64kA, rated operational power at AC- 23, 400 V 15kW, Switching capacity at 400 V 15kW, Rated conditional short-circuit current Iq 80kA, Number of poles 3, Number of auxiliary contacts as NC contact 1, Number of auxiliary contacts as NO contact 1, Number of auxiliary contacts as changeover contact 0, Device design Complete device in housing, Suitable for floor mounting, Color of the actuating element red, design of the actuating element door-coupling rotary drive, lockable, connection type main circuit screw connection, protection (IP), on the front IP65, degree of protection (NEMA) other, main switch, range: main switch, maintenance switch, repair switch, type identifier: P1, STOP function: EMERGENCY STOP function, with red rotary handle and yellow locking ring, information on the scope of delivery: auxiliary switch contact or neutral conductor can be retrofitted., 3-pole, lockability: lockable in 0 position, degree of protection: IP65, design: surface-mounted, rated operational power AC-23A, 50 - 60 Hz 400 V: P = 15 kW, rated continuous current: Iu = 32 A, standards and regulations: IEC/EN 60947, VDE 0660, IEC/EN 60204, load-break switch according to IEC/EN 60947-3

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

