



Main switch emergency stop/intermediate structure - Safety switch 3-p 13kW P1-25/V/SVB



Eaton
P1-25/V/SVB
055335
4015080553359 EAN/GTIN

43,98 USD excl. VAT**
plus shipping



4-5 days* (USA)

Emergency stop main switch/intermediate P1-25/V/SVB design as main switch, design as maintenance/repair switch, design as EMERGENCY STOP device, number of switches 1, max. rated operating voltage U_e at AC 690V, rated operating voltage 690 ... 690V, rated uninterrupted current I_u 25A, rated uninterrupted current at AC-23, 400 V 25A, rated uninterrupted current at AC-21, 400 V 25A, rated operational power at AC-3, 400 V 7.5kW, rated short-time withstand current I_{cw} 0.64kA, rated operational power at AC-23, 400 V 13kW, switching capacity at 400 V 13kW, conditional rated short-circuit current I_q 80kA, number of poles 3, number of auxiliary contacts as NC contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as changeover contact 0, device design built-in device fixed installation technology, color of the actuating element red, design of the Actuating element door-coupling rotary drive, lockable, connection type main circuit screw connection, degree of protection (IP), on the front IP65, degree of protection (NEMA) 12, mains switch, range: main switch, maintenance switch, repair switch, type code: P1, STOP function: EMERGENCY STOP function, with red rotary handle and yellow locking collar, information on scope of delivery: auxiliary switch contact or neutral conductor can be retrofitted., 3-pole, lockability: lockable in 0 position, degree of protection: front IP65, design: sandwich, rated operational power AC-23A, 50 - 60 Hz 400 V: P = 11 kW, rated continuous current: I_u = 25 A, standards and regulations: IEC/EN 60947, VDE 0660, IEC/ EN 60204, CSA, UL, load-break switch according to IEC/EN 60947-3, NEMA12

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

