



Current monitoring relay 0.05-10A AC/DC 1W 3UG4622-1AW30



Siemens
3UG4622-1AW30
 4011209642423 EAN/GTIN

128,22 USD excl. VAT**
 plus shipping



4-5 days* (USA)

Current monitoring relay 0.05-10A AC/DC 1W 3UG4622-1AW30 Design of the electrical connection screw connection, with removable terminals, 1-phase undercurrent possible, 1-phase overcurrent possible, contains DC voltage undercurrent function, contains DC voltage overcurrent function, function DC window, rated control supply voltage Us at AC 50 Hz 20.4 ... 264V, rated control supply voltage Us at AC 60 Hz 20.4 ... 264V, rated control supply voltage Us at DC 20.4 ... 264V, type of voltage for actuation AC/DC, current measuring range 0.05 ... 15A, min. adjustable response delay time 0.1s, max. permissible response delay time 20s, min. adjustable off-delay time 0.1s, max. permissible off-delay time 20s, number of contacts as NC contacts 0, number of contacts as NO contacts 0, number of contacts as changeover contact 1, width 22.5 mm, height 92 mm, depth 91 mm, digital monitoring relay, current monitoring, 22.5 mm from 0.05-10 A AC/DC overshoot and undershoot AC/DC 24 to 240 V DC and AC 50 to 60 Hz start-up and transient delay. 0.1 to 20 s hysteresis 0.01 to 5 A 1 changeover contact with or without fault memory Screw connection Successor product for 3UG3522-1AL20, 3UG3522-1AG20 and 3UG3522-1AC48-0AA1 SIRIUS 3UG4 digitally adjustable current monitoring relay for monitoring currents for overshoot and undershoot, e.g. B. to ensure the functionality of electrical consumers or for wire break monitoring. Worldwide use through international certificates. The relay can be variably set to overshoot or window monitoring. Delay times and RESET behavior can be freely parameterized. Less space required in the control cabinet thanks to a narrow overall width. Reliable diagnostics by displaying the actual value and status messages. All versions with removable connection terminals. In addition to screw connection technology, the devices are also available with spring-loaded connections for a quick, maintenance-free and vibration-proof connection. They are also available in different voltages, optionally with IO-Link. The comprehensive range of accessories, such as device identification labels, push-in lugs and cover caps, is the same for all relays. SIRIUS relays - a program for all cases.

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

