

Item Number EB10849729

×

https://www.eibabo.us/berker/socket-with-grounding-contact-q.1-po-socket-outlet-receptacle-67657660 89-eb10849729



Socket with grounding contact Q.1 po - Socket outlet (receptacle) 6765766089

**Berker** 6765766089 4011334313557 EAN/GTIN

## 6,95 USD excl. VAT\*\*

plus **shipping** 

15-16 days\* (USA)

Socket with protective contact Q.1 po 6765766089 Version SCHUKO, protective contact, protective earth contact round, number of active contacts (round) 2, number of active contacts (flat) 0, number of units 1, number of modules (with modular design) 0, number of sockets switchable 0, number of phases 1, imprint/identification without imprint, connection type screw terminal, with increased contact protection, color white, RAL number (similar) 9010, insulated installation, special power supply without special power supply, type of installation flush-mounted, type of attachment claw attachment, material plastic, Material quality Duroplast, halogen-free, surface untreated, design of the surface matt, rated current 16A, rated voltage 250V, frequency 50 ... 60Hz, suitable for protection class (IP) IP20, impact resistance IK02, device width 71mm, device height 71mm, device depth 42mm, central plate cover, socket with protective contact pin and increased BS Q.1/Q.3 polar white, velvety. Q.1 Program description (long text) Switch program made of Duroplast, scratch-resistant, polar white (similar to RAL 9010). Frame 1x to 5x, can be used vertically or horizontally. Square basic shape with rounded corners with a 4 mm radius of curvature, with a flat geometry and a velvety surface. Rockers/covers with an edge length of 58 mm x 58 mm and rounded corners with a radius of 2 mm. The socket center pieces and many other center pieces form a flush surface with the frame. Installation devices can be used in some cases with a separate sealing set that is water-protected UP IP 44. Possibility of labeling using frames that can be labeled, vertically and horizontally, 1x to 5x. Abrasion-resistant labeling of products using laser technology. Can be illuminated according to workplace regulations. The material used is halogen-free and UV-stable, the surfaces are easy to clean and are resistant to disinfectants. Over 270 applications.

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

