



Fan 19W, 180cbm/h, IP34 - Small-room ventilator surface mounted ECA 120 K



Maico
ECA 120 K
0084.0009
4012799840091 EAN/GTIN

189,52 USD excl. VAT**
plus shipping



4-5 days* (USA)

Fan 19W, 180cbm/h, IP34 ECA 120 K Mains frequency 50Hz, rated voltage 230V, surface-mounting type, housing material plastic, color white, volume flow 180m³/h, protection class (IP) IP34, nominal width 120mm, other composition, axial design, ventilation direction , Version with delay timer: With electrically operated internal lock. Switch-on delay approx. 50 seconds. Follow-up time approx. 6 minutes. Not speed controllable. High delivery volume despite compact size. Combines large delivery volume with pressure strength. Thermal overload protection. Housing made of impact-resistant plastic. Protection class II. With VDE-GS mark, exception: ECA 120 24 V. With protective seals to prevent the ingress of condensation when installed in the ceiling. Speed control optional for standard ECA fans. Color traffic white similar to RAL 9016. Motor: Robust motor with ball bearings, maintenance-free. Suitable for continuous operation. Assembly instructions: Quick and easy dismantling of the cover. Quickly attach the fan to the pipe using 2 clamping springs. Electrical connection: Electrical connection either surface-mounted or flush-mounted. Safety instructions: ECA 120 devices with protection class IP 45 can be used in protection area 1 according to DIN VDE 0100-701. For details see planning information. Article: ECA 120 KVZ, version: delay timer, delivery volume: 180 m³/h, speed: 2600 1/min, speed controllable: no, reversibility: no, voltage type: alternating current, rated voltage: 230 V, mains frequency: 50 Hz / 60 Hz, power consumption: 19 W, IMax: 0.14 A, protection class: IP 34, power supply cable: 5 / 1.5 mm² location: wall, installation type: surface-mounted, installation position: any, material: plastic, color: traffic white, similar to RAL 9016, weight: 0.9 kg, flap type: electric, nominal width: 120 mm, width: 171 mm, height: 171 mm, depth: 114 mm, conveyor temperature at IMax: 40 °C, follow-up time: 6 min, switch-on delay: 50 s , Sound pressure level: 36 dB(A) / distance 3 m, free field conditions

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt[®]



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo[®] and eibmarkt[®] are registered trademarks of EIBMARKT[®] GmbH holding company (www.eibmarkt.de). eibabo[®] is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT[®] GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo[®] the Smart Home technology shop
eibabo[®] electronics cheap online order
eibabo[®] electric appliances buy online

